

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 3 -

April 28, 2006

Amendment to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1 (original). A valve for controlling fluid flow, said valve comprising:

an inlet duct;

an outlet duct in fluid communication with said inlet duct;

a seat positioned between said inlet duct and said outlet duct;

a pressure chamber positioned in facing relation with said seat;

a closure member positioned between said pressure chamber and said seat and having a seat engaging surface facing said seat, said closure member being pivotable about an axis to bring said seat engaging surface into and out of sealing engagement with said seat to open and close said valve; and

a diaphragm sealingly positioned between said pressure chamber and said closure member and attached thereto, said diaphragm being flexible and transferring pressure from said pressure chamber onto said closure member, said closure member being pivoted into sealing engagement with said seat when said pressure chamber is pressurized, thereby closing said valve, said closure member being pivotable out of engagement with said seat when said pressure chamber is depressurized, thereby allowing said valve to open.

2 (original). A valve according to Claim 1, wherein said seat has a non-circular shape.

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 4 -

April 28, 2006

3 (original). A valve according to Claim 2, wherein said seat has an elliptical shape.

4 (original). A valve according to Claim 3, wherein said inlet duct is substantially coaxially aligned with said outlet duct.

5 (original). A valve according to Claim 4, wherein said seat is angularly oriented relatively to said inlet and outlet ducts.

6 (original). A valve according to Claim 1, wherein said seat comprises a loop having an inner and an outer perimeter, a first projection extending along said inner perimeter, and a second projection extending along said outer perimeter, both of said projections facing said valve closure member for sealing engagement therewith upon pivoting of said valve closure member, said first and second projections being in spaced apart relation to each other and defining a space between them.

7 (original). A valve according to Claim 6, wherein said loop is comprised of a flexible, resilient material.

Claim 8 (canceled).

9 (original). A valve according to Claim 6, further comprising an aperture extending through said seat and providing fluid communication between said space and a region external to said valve.

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 5 -

April 28, 2006

10 (original). A valve according to Claim 9, wherein said aperture is vented to the ambient.

Claims 11-15 (canceled).

16 (original). A valve for controlling fluid flow, said valve comprising:

an inlet duct;

an outlet duct in fluid communication with said inlet duct;

a seat positioned between said inlet duct and said outlet duct;

a closure member positioned between said inlet duct and said outlet duct and having a seat engaging surface facing said seat, said closure member being pivotable about an axis to bring said seat engaging surface into and out of sealing engagement with said seat to open and close said valve; and

a loop mounted on one of said seat and said valve closure member, said loop having an inner and an outer perimeter, a first projection extending along said inner perimeter, and a second projection extending along said outer perimeter, both of said projections facing the other of said seat and said valve closure member for sealing engagement therewith upon pivoting of said valve closure member, said first and second projections being in spaced apart relation to each other and defining a space between them.

17 (original). A valve according to Claim 16, wherein said loop is mounted on said seat.

18 (original). A valve according to Claim 17, wherein said loop comprises a flexible, resilient material.

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 6 -

April 28, 2006

Claims 19-22 (canceled).

23 (original). A valve according to Claim 16, wherein said seat has a non-circular shape.

24 (original). A valve according to Claim 23, wherein said seat has an elliptical shape.

Claim 25 (canceled).

26 (original). A valve according to Claim 24, wherein said seat is angularly oriented relatively to said inlet and outlet ducts.

27 (original). A valve according to Claim 16, further comprising an aperture extending through said seat and providing fluid communication between said space and a region external to said valve when said seat engaging surface engages said seat.

28 (original). A valve according to Claim 27, wherein said aperture is vented to the ambient.

29 (original). A valve according to Claim 16, further comprising:

a pressure chamber positioned adjacent to said closure member; and

a diaphragm sealingly positioned between said pressure chamber and said closure member and attached thereto, said diaphragm being flexible and transferring pressure from said pressure chamber onto said closure member, said closure

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 7 -

April 28, 2006

member being pivoted into sealing engagement with said seat when said pressure chamber is pressurized, thereby closing said valve, said closure member being pivotable out of engagement with said seat when said pressure chamber is depressurized, thereby allowing said valve to open.

30 (original). A sprinkler system for fire suppression, said system comprising:

a source of pressurized water;

a plurality of sprinkler heads for distributing said water;

a piping network providing fluid communication between said source of pressurized water and said sprinkler heads;

a first valve connected in said piping network between said source of pressurized water and said sprinkler heads, said first valve comprising:

an inlet duct connected to said piping network;

an outlet duct connected to said piping network, said outlet duct being in fluid communication with said inlet duct;

a seat positioned between said inlet duct and said outlet duct;

a pressure chamber positioned in facing relation with said seat;

a first conduit providing fluid communication between said source of pressurized water and said pressure chamber;

a second conduit providing fluid communication between said pressure chamber and the ambient;

a closure member positioned between said pressure chamber and said seat and having a seat engaging surface facing said seat, said closure member being pivotable about an

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 8 -

April 28, 2006

axis to bring said seat engaging surface into and out of sealing engagement with said seat to open and close said valve;

a diaphragm sealingly positioned between said pressure chamber and said closure member and attached thereto, said diaphragm being flexible and transferring pressure from said pressure chamber onto said closure member, said closure member being pivoted into sealing engagement with said seat when said pressure chamber is pressurized, thereby closing said valve, said closure member being pivotable out of engagement with said seat when said pressure chamber is depressurized, thereby allowing said valve to open; and

a second valve positioned in said second conduit and regulating the flow of water from said pressure chamber to the ambient to open and close said valve.

31 (original). A sprinkler system according to Claim 30, wherein said seat has a non-circular shape.

32 (original). A sprinkler system according to Claim 31, wherein said seat has an elliptical shape.

33 (original). A sprinkler system according to Claim 32, wherein said inlet duct is substantially coaxially aligned with said outlet duct.

34 (original). A sprinkler system according to Claim 33, wherein said seat is angularly oriented relatively to said inlet and outlet ducts.

35 (original). A sprinkler system according to Claim 30, wherein said seat comprises a loop having an inner and an

RESPONSE TO OFFICE ACTION
DATED DECEMBER 15, 2005

Appln No. 10/759,714

- 9 -

April 28, 2006

outer perimeter, a first projection extending along said inner perimeter, and a second projection extending along said outer perimeter, both of said projections facing said valve closure member for sealing engagement therewith upon pivoting of said valve closure member, said first and second projections being in spaced apart relation to each other and defining a space between them.

36 (original). A sprinkler system according to Claim 35, wherein said loop is comprised of a flexible, resilient material.

Claim 37 (canceled).

38 (original). A sprinkler system according to Claim 35, further comprising an aperture extending through said seat and providing fluid communication between said space and a region external to said valve.

39 (original). A sprinkler system according to Claim 38, wherein said aperture is vented to the ambient.

40 (original). A sprinkler system according to Claim 38, further comprising an alarm in fluid communication with said aperture, said alarm being triggered by flow of said water through said aperture upon opening of said first valve.

Claims 41-48 (canceled).